

Marshall

BROADCAST & PRO AV

M-LYNX-702 V.3

Dual 7" LCD Display



High resolution 1280 x 800 bright, colorful display with no-compromise input selections for each screen

Digital inputs: HDMI, 3GSDI with loop-through (auto selects HDSDI/SDI)

Special features: Selectable markers, 1:1 pixel mapping, Over scan and H/V delay modes, View individual colors

Audio de-embedding and monitoring via front panel headphone jacks

Red, Green, Yellow in-screen Tally borders

Slim design and 3RU size

Power via 4-pin XLR jack or use included 12-volt universal supply

Selectable English and Spanish on-screen displays

The **M-LYNX-702 V.3** Dual 7" LCD Display is a feature-packed, economical solution perfect for fly-packs, control rooms, routing rooms and countless other video system applications. Dual looping video inputs set this product apart from similar-looking products. With the M-LYNX-702, you are not limited to the single SDI connector you may find on competitor models. Standard power and tally connections as well as a logical menu structure make this display an easy choice for flexible system designs.

Features, specifications, pricing, and dimensions are subject to change without notice.

Physical appearance of products may vary slightly from images shown on this document. Please visit our website for updates and information.

Number of Panels	2
Panel Size	7" rack mount, 3RU High
Resolution (Pixels)	1280 x 800
Aspect Ratio	16 : 10
Active Area	149.26 (W) mm x 93,6 (V) mm
Backlight	LED
Viewing Angle	178°
Brightness (in cd/m²)	250
Contrast Ratio	800:1
Digital Video Inputs	3GSDI x 1 (conforms to SMPTE-292M, 259M, 424M) HDMI x 1 (with loop-out)
Audio Inputs	Accepts HDMI and SDI embedded audio
Audio Outputs	Front panel 3.5mm stereo headphone jack
Control Inputs	Ethernet remote control port Tally 9-pin D-Sub port for GPI input Mini USB Service Port
Power	11 to 17 volts DC, 12-volts typical via 5.5mm jack or 4-pin XLR
Compliance	FCC-Class A, CE, RoHS
Dimensions	19" W x 5.2" H x 1" D / 482.6mm x 132mm x 25.4mm
Weight	4 lbs / 1.85 Kg
Warranty One year standard, two years with product registration	